



Support Product

Description

An acrylic protective finishing wax in an acrylic emulsion for Venetian plasters.

Recommended Use

Interior commercial, hospitality, military, educational and residential applications; used in connection with PermaTone Walltextures.

Colors

Clear.

Packaging

1 quart pail: 1.25 lbs. gross.

Approximate Coverage

250-300 ft² per quart.

Equipment

Stainless steel trowel with rounded corners and beveled edges.

Surface Preparation

Venetian plaster finishes shall be fully dry and cured prior to application of Ceraplus.

Application Instructions

Trowel apply the material in a thin even coat using random short strokes. If a gloss finish is desired, burnish immediately with trowel. Additional burnishing increases gloss. Do not overburnish.

Properties

Initial set in 1 hour, cure in 72 hours, at 70°F and 50% RH.

Benefits

Water based; environmentally safe; vapor permeable; moisture resistant, grease resistant; adds durability in baths and kitchens.

Limitations

Skilled application required; not compatible with solvent based products or cleaners; apply in temperatures between 60°F and 85°F; protect face and eyes; use in well ventilated areas; for use on interior wall and ceiling surfaces only; do not mix with other products.

Maintenance

To clean, use a soft sponge or damp cloth and a mild soap and water solution.

Warranty

10 years material warranty against delamination.

- Always prepare a mock-up of minimum 4' x 4' for approval prior to application to subject wall areas. The mock-up serves two purposes, to establish coverage and material requirements and to establish owner's expectations as to the appearance of the texture. Coverage varies according to substrate conditions and applicator technique and skill level.
- The application instructions described herein represent the most typical methods currently used, but are in no way intended to restrict the designer, contractor or faux finisher in terms of creating new patterns, effects or textures using PermaTone products. Instructions as to surface preparation and reduction should be followed precisely, however, in order not to void the warranty.
- PermaTone products should never be mixed with other materials, with the exception of clean, potable water, and then only where indicated as acceptable in this or other PermaTone product information documents.
- Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document. PermaTone assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project.
- Most equipment described in this document may be purchased from PermaTone or its distributors.

Ceraplus