



## Support Product

### Description

An acrylic, clear, semi-gloss, permeable and mildew resistant wall surface sealer.

### Recommended Use

Interior commercial, military, educational and residential applications; as a sealer for PermaTone Wall textures where semi-gloss finish, enhanced cleanability or more hydrophobic surface is required; as a sealer for painted and masonry surfaces.

### Colors

Clear.

### Packaging

5 gallon pail: 39 lbs. net, 41.8 lbs. gross.

### Approximate Coverage

1000-1200 ft<sup>2</sup> per 5 gallon bucket.

### Equipment

Brush, roller or spray equipment.

### Surface Preparation

Surfaces must be clean, dry and free of dust, grease or loose material.

### Application Instructions

Uniformly apply VitroSeal by brush, roller or spray equipment. Apply two coats, allowing 6 hours drying time between coats.

### Properties

Initial set in 1 hour, cure in 24 hours, at 70°F and 50% RH.

### Benefits

Water based; environmentally safe; vapor permeable, hydrophobic, cleanable.

### Limitations

Skilled application required; not compatible with solvent based products or cleaners; apply in temperatures between 60°F and 85°F; protect face and eyes; use in well ventilated areas; for use on wall and ceiling surfaces only; do not mix with other products; do not water down material; avoid constant and excessive buildup of moisture in the substrate.

### Maintenance

To clean, use a soft sponge or damp cloth and a mild soap and water solution.

### Warranty

5 years material warranty against delamination and mildew growth.

- Always prepare a mock-up of minimum 4' x 4' for approval prior to application to subject wall areas. The mock-up serves two purposes, to establish coverage and material requirements and to establish owner's expectations as to the appearance of the texture. Coverage varies according to substrate conditions and applicator technique and skill level.
- The application instructions described herein represent the most typical methods currently used, but are in no way intended to restrict the designer, contractor or faux finisher in terms of creating new patterns, effects or textures using PermaTone products. Instructions as to surface preparation and reduction should be followed precisely, however, in order not to void the warranty.
- PermaTone products should never be mixed with other materials, with the exception of clean, potable water, and then only where indicated as acceptable in this or other PermaTone product information documents.
- Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document. PermaTone assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project.
- Most equipment described in this document may be purchased from PermaTone or its distributors.

# VitroSeal