

Pintufondo

PermaTone[®]
by  **COREV**[®]



PermaTone® Pintufondo

Pintufondo A vapor permeable, all acrylic interior primer formulated with silica fillers to enhance surface grip and form an excellent bonding surface between the substrate and the finish coat. PINTUFONDO is highly effective against mold and mildew.

RECOMMENDED USE

PINTUFONDO is used as a wall primer for PERMATONE texture coatings.

COVERAGE

800 to 1000 ft² per 5 gal. pail. Porosity of substrate and application technique can affect coverage.

COLORS

PINTUFONDO can be tinted to almost any custom color.

PACKAGING

5 gal. pail: 54 lbs. net, 56.8 lbs. gross.

PROPERTIES

Drying Time

Initial Set: 4 hrs. @ 70°F, 50% RH

Cure: 24 hrs. @ 77°F, 50%RH

REDUCTION

Use potable water. Don't exceed 10% by volume.

APPLICATION

Surface Preparation

Walls must be prepared to be paint ready.

Surfaces must be clean, dry and free of dust, grease or other materials that may affect bonding.

Previously painted surfaces must be scraped to remove all loose paint.

Interior drywall must be taped floated and sanded using normal interior drywall finishing procedures. Use COREVMIX to repair minor drywall damage and skim over residual wall covering adhesive.

Mixing Instructions

Stir to a homogeneous consistency.

Application Procedures

Can be applied with brush, roller or spray equipment.

CLEAN UP

Clean equipment with water while PINTUFONDO is still wet.

STORAGE

Store PINTUFONDO in its original container at temperatures not less than 40°F or greater than 110°F. Store out of direct sunlight. Do not stack pails more than three high.

SHELF LIFE

Approximately one year if stored properly.

MAINTENANCE

Coatings may be cleaned of minor deposits with a mild soap and water solution.

WARRANTY

PINTUFONDO is conditionally warranted for 10 years against delamination, color fading, and mildew growth. FOR COMPLETE INFORMATION, CONSULT PERMATONE'S LONG FORM SPECIFICATIONS AND PRODUCT WARRANTIES. This warranty does not apply to any party constituting a "consumer" for purposes of the Magnuson-Moss Warranty Act. All other warranties, whether expressed or implied, including without limitation any warranty of merchantability or fitness for purpose are expressly disclaimed.

LIMITATIONS

- Do not use for exterior application.
- Do not mix with other products.
- Surface air and substrate temperatures must be 40°F or higher during application and for a period of 24 hours thereafter.
- PINTUFONDO is not compatible with solvent base products or cleaners.
- Use in well ventilated areas. Protect all adjacent surfaces, door frames, windows, etc.) Do not water down material. Prepare metal surfaces such as corner bead with rust inhibitors prior to PINTUFONDO application.
- This product requires skilled application.
- Use eye and face protection.
- Avoid constant moisture in the wall cavity behind the coating.



PermaTone, Inc.
11620 Brittmoore Park Drive
Houston, Texas 77041
713/937-3437 TEL
713/937-9765 FAX
800/944-4911 TOLL FREE
www.permatone.com

PermaTone, the PermaTone logo, Corev, and the Corev logo are registered trademarks of Corev, Inc.