

PermaTone
by COREV

Sottofondo



PermaTone Sottofondo

Sottofondo An acrylic, clear, permeable, and mildew resistant interior or exterior primer sealer and bond enhancer.

RECOMMENDED USE

Interior or exterior primer sealer for sealing new or previously painted masonry and drywall surfaces. Adheres well to semi-gloss surfaces and acts as a bonding primer on substrates such as ceramic tile, glazed brick, and non-ferrous metal surfaces.

COVERAGE

Each 5 gal. pail provides approx. 1000-1200 ft² of coverage over new drywall. Surface porosity and job conditions may affect coverage.

PACKAGING

1 gal. pail: 7 lbs. net, 7.5 lbs. gross
5 gal. pail: 36 lbs. net, 38.8 lbs. gross

PROPERTIES

Drying Time

Initial Set: 2 hrs. @ 77°F, 50% RH
Cure: 24 hrs. @ 77°F, 50% RH

REDUCTION

Not required or recommended.

EQUIPMENT

Can be applied by brush or roller. Spray application is not recommended.

APPLICATION

Surface Preparation

Surface must be clean, dry and free of dust, dirt, grease or loose material.

Application Procedures

Uniformly apply SOTTOFONDO by brush or roller.

Let SOTTOFONDO dry for 24 hours before applying topcoat.

STORAGE

Store SOTTOFONDO in its original container at temperatures not less than 40°F (4°C) or greater than 110°F (43°C). Store in covered space, out of direct sunlight. Do not stack pails more than three high.

SHELF LIFE

Approximately one year if stored properly.

WARRANTY

SOTTOFONDO is conditionally warranted for 10 years against delamination and mildew growth. FOR COMPLETE INFORMATION, CONSULT THE MANUFACTURERS LONG FORM SPECIFICATIONS AND PRODUCT WARRANTIES. This warranty does not apply to any party constituting a "consumer" for purposes of the Magnuson-Moss Warranty Act. All other warranties, whether expressed or implied, including without limitation any warranty of merchantability or fitness for purpose are expressly disclaimed.

LIMITATIONS

- Surface air and substrate temperatures must be 40°F or higher during application and for a period of 24 hours thereafter.
- SOTTOFONDO is not compatible with solvent base products or cleaners.
- Use in well ventilated areas. Protect all adjacent surfaces (doorframes, windows, etc.) adequately. Do not water down material. Prepare metal surfaces such as corner bead with rust inhibitors prior to Sottofondo application.
- Use eye and face protection.
- Avoid the constant and excessive buildup of moisture in the substrate.



PermaTone, Inc.
11620 Brittmoore Park Drive
Houston, Texas 77041
713/937-3437 TEL
713/937-9765 FAX
800/944-4911 TOLL FREE
www.permatone.com

PermaTone, the PermaTone logo, Corev, and the Corev logo are registered trademarks of Corev, Inc.