

PermaTone Agostino™

Agostino

A permeable Venetian Stucco with a smooth honed finish, AGOSTINO is a decorative finish reminiscent of travertine. It is formulated with acrylic resins, organic and inorganic pigments, mineral fillers and chemical additives that enhance the coating's performance.

RECOMMENDED USE

AGOSTINO is the ideal choice for elegant interior wall spaces where visually dramatic glossy old-world accents are desired. Layers of color create depth and texture that greatly enhance either classical or contemporary settings.

COVERAGE

Each gallon provides approximately 60-70 ft² of coverage with a two-coat application over a smooth surface.

PROPERTIES

Drying Time

Initial Set: 2 hrs @77°F, 50% RH

Cure: 72 hrs @ 77°F, 50% RH

Packaging

1 GL pail -12 lbs. net, 12.5lbs. gross

5 GL pail- 60 lbs.net, 62.5lbs. gross

Thinning Not required or recommended.

EQUIPMENT

Stainless steel trowel with rounded corners and beveled edges, plastic float and flexible metallic spatula.

APPLICATION

Surface Preparation

Walls must be prepared to be paint ready. Surfaces must be clean, dry and free of dust, grease or other materials that may affect bonding.

Previously painted surfaces must be scraped to remove all loose paint.

Interior drywall must be taped, floated and sanded using normal interior drywall finishing procedures. Use COREVMIX surface leveler to repair minor drywall damage.

Material Preparation

Manually mix AGOSTINO until homogeneous.

Application Procedures

Remove all dust with a moist cloth. Using a roll or spray equipment, prime the surface with PINTUFONDO acrylic primer.

Using a stainless steel trowel, apply the first layer of AGOSTINO, using long strokes with irregular pattern avoiding ANY material buildup. Each coat thickness should not exceed 16-18 mils (the thickness of the aggregate). Allow the first coat to dry 6-8 hrs. before applying a second coat in the same manner as the first. Allow the AGOSTINO to set up for approximately 5-10 minutes before beginning to texture. To achieve the *smooth texture, desire gloss* and mottled appearance, use a stainless steel trowel for dark and medium colors or plastic trowel for light or pastel colors and repeatedly float the surface by pressing down and sliding the trowel's edge over the surface holding a 5° to 10° angle to the surface until it becomes smooth and shiny.

The final appearance depends on the hand motion and experience of the individual applicator.

STORAGE

Store AGOSTINO in its original container at temperatures not less than 40°F (4°C) or greater than 90°F (43°C). Store in covered space, out of direct sunlight. Do not stack pails more than three high.

SHELF LIFE

Approximately 12 months if stored properly.

MAINTENANCE

Surface may be cleaned of minor stains with a damp cotton cloth.

WARRANTY

AGOSTINO is conditionally warranted for 10 years against delamination and color fading. FOR COMPLETE INFORMATION CONSULT PERMATONE'S LONG-FORM SPECIFICATIONS AND PRODUCT WARRANTIES. This warranty does not apply to any party constituting a "consumer" for purposes of the Magnuson-Moss Warranty Act. All other warranties, whether expressed or implied, including without limitation any warranty of merchantability or fitness for purpose are expressly disclaimed.

LIMITATIONS

This product requires skilled application.

Surface air and substrate temperature must be 40°F or higher during application and for 24 hrs thereafter.

AGOSTINO is not compatible with solvent-based coatings and cleaners.

Wear face and eye protection during application.

Use in a well ventilated area.



PermaTone, Inc.

11620 Brittmoore Park Drive Houston,
Texas 77041 832/243-0787 TEL

713/937-9765 FAX

800/944-4911 TOLL FREE

www.permatone.com