

PermaTone CorevLime™

COREVLIME

COREVLIME™ is a premixed acrylic textured finish coating. COREVLIME provides a finish that is durable, colorfast and easy to maintain. It is formulated with acrylic copolymers, organic and inorganic pigments, mineral fillers and chemical additives that enhance the performance of the coating.

Recommended Use

COREVLIME is used in exterior and interior applications. It is applied over COREVSAND or any coarse finish

Coverage

Each 5 gallon bucket provides approximately 180 to 200 square feet. Variation in substrate, details, and individual application technique will affect the coverage.

Colors

PERMATONE will match other colors specified by the client and provide samples for approval. Colors may vary slightly from batch to batch. The applicator should exercise care in reviewing the lot numbers on each bucket so that all adjacent areas are coated with the same batch.

Properties

Drying Time

Initial Set: 2 hours in 77°F, 50% RH
Cure: 72 hours @ 77°F, 50% RH

VOC Compliance:

COREVLIME complies with all known regulations limiting the Volatile Organic Compound (VOC) content of architectural coatings and sealers.

Packaging

(5 gallon bucket)
64 lbs. per bucket net
67 lbs. per bucket gross

Equipment

Stainless steel trowel with rounded corners and beveled edges; Plastic float.

Application

Surface Preparation

COREVSAND must be completely dry and free of dust, dirt, grease, oil or other pollutants prior to application of COREVLIME. COREVLIME is tinted to the same color as the COREVSAND that serves as its substrate.

Mixing Instructions

Prior to application to the substrate, COREVLIME should be stirred with a slow speed drill and paddle. The workability of COREVLIME may be adjusted by adding a small amount of water (8 oz. or less per bucket). No other additives should be put into the finish. Excessive dilution will affect color stability and bond strength.

Application Procedures

Using a stainless steel trowel, extend the material evenly over the surface of the COREVSAND. Turn the trowel to an approximate 20° angle to the surface of the coating, and pull the material fairly tight to the surface of the COREVSAND.

A second installer follows the first, holding a plastic float flat to the surface, and moving the float in random circular motions and a light touch to produce the texture. This second installer gives COREVLIME its final appearance.

Storage

Store COREVLIME in its original containers at temperatures not less than 40°F (4°C) or greater than 110°F (43°C). Store out of direct sunlight. Do not stack buckets more than 3 high.

Shelf Life

Approximately 1 year if properly stored.

Maintenance

Coatings may be cleaned of minor deposits with a mild soap and water solution. Major soiled surfaces may be recoated with PINTUFONDO acrylic interior flat latex paint. Surface mildew can be cleaned by rolling the surface with a 3:1 solution of clean potable water and household bleach.

Warranty

COREVLIME is conditionally warranted for 10 years against delamination, color fading, and mildew growth. This warranty does not apply to any party constituting a “consumer” for purposes of the Magnuson-Moss Warranty Act. All other warranties, whether expressed or implied, including without limitation any warranty of merchantability or fitness for purpose, are expressly disclaimed.

LIMITATIONS

- For use on interior wall and ceiling surfaces only.
- Patching limitations standard to applied coatings.
- This product requires skilled application.
- Surface air and substrate temperatures shall be 60°F to 85°F during application and for a period of 24 hours thereafter.
- QuartzSilco is not compatible with solvent base products or cleaners.
- Use in well ventilated areas.
- Protect all adjacent surfaces (door frames, windows, etc.) adequately.
- Do not water down material.
- Do not apply over quickset joint compound.
- Prepare metal surfaces such as corner bead with rust inhibitors prior to application of CorevLime.
- Always wear appropriate eye and skin protection when using this product.
- Harmful if swallowed.
- Avoid constant moisture in the wall cavity behind the coating.

Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document. PermaTone assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project.

Safety

ALWAYS WEAR APPROPRIATE EYE AND SKIN PROTECTION WHEN USING THIS PRODUCT. HARMFUL IF SWALLOWED. BEFORE APPLYING THE PRODUCTS REFER TO THE COMPLETE LONG FORM SPECIFICATIONS OF THE PERMATONE INC PRODUCTS.

The logo for PermaTone, featuring the word "Perma" in a bold, blue, sans-serif font and "Tone" in a red, cursive script font.

PermaTone, Inc.

11620 Brittmoore Park Drive
Houston, Texas 77041
713/937-3437 TEL
713/849-9114 FAX
877/737-6286 TOLL FREE
www.permatone.com

Made in the U.S.