

PermaChiffon™

Chiffon

A permeable acrylic stucco with a smooth old-world matte finish, CHIFFON is a paste composed of fine silica and other mineral fillers that create a tight surface matrix. It is formulated with acrylic copolymers, organic and inorganic pigments, fillers and chemical additives that enhance the coatings performance. CHIFFON is highly permeable and mildew resistance.

RECOMMENDED USE

CHIFFON is an ideal choice for elegant interior wall spaces where visually dramatic and old-world accents are desired, and where a hard traffic resistant surface is required. Brushed, troweled or sprayed, CHIFFON can be floated to a smooth surface, or textured and combined with CASTELLO and/or RIFLEXI to emulate the elegant flow of fabric.

COVERAGE

Each gallon provides approximately 100-120 ft² of coverage with an approximate 30-35 mil application over a smooth surface.

PROPERTIES

Drying Time

Initial Set: 2 hrs. @ 77°F, 50% RH

Cure: 72 hrs. @ 77°F, 50% RH

PACKAGING

1 gal. pail: 12 lbs. net, 12.5 lbs. gross

5 gal. pail: 60 lbs.net, 62.5 lbs. gross

REDUCTION

Not required.

If reduction is desired to adjust thickness for spray application, use clean water and do not exceed 8% by volume.

EQUIPMENT

Stainless steel trowel with rounded corners and beveled edges, plastic float and flexible metallic spatula. Spray equipment. Paint and texture rollers, brushes and rags

VOC Compliance:

Chiffon complies with all known regulations limiting the Volatile Organic Compound (VOC) content of architectural coatings and sealers. ASTM D3960 19g/L or .16lb/gal

APPLICATION

Surface Preparation

- Walls must be prepared to be paint ready.
 - Surfaces must be clean, dry and free of dust, grease or other materials that may affect bonding.
 - Previously painted surfaces must be scraped to remove all loose paint.
 - Interior drywall must be taped, floated and sanded using normal interior drywall finishing procedures. Use COREVMIX surface leveler to repair minor drywall damage.
- WARNING: Surface imperfections might show through the final finish.

Material Preparation

Manually mix CHIFFON until homogeneous.

Application Procedures

Using a brush, roll or spray equipment, **Paint-prime** over the surface with PINTUFONDO. CHIFFON is a homogeneous fine paste which can be textured to the designer's and applicators desire. Do not exceed a thickness of 40 mils per layer.

Ideally the dry CHIFFON surface will be enhanced with Permatone's CASTELLO acrylic glaze or RIFLEXI metallic and pearlescent finish.

The final appearance depends on the experience of the individual applicator.

STORAGE

Store CHIFFON in its original container at temperatures not less than 40°F (4°C) or greater than 100°F (37°C). Store in covered space, out of direct sunlight.

Do not stack pails more than three high.

SHELF LIFE

Approximately six months if stored properly.

MAINTENANCE

Surface may be cleaned of minor stains with a damp cotton cloth.

WARRANTY

CHIFFON is conditionally warranted for 10 years against delamination and color fading. FOR COMPLETE INFORMATION CONSULT PERMATONE'S LONG FORM SPECIFICATIONS AND PRODUCT WARRANTIES. This warranty does not apply to any party constituting a "consumer" for purposes of the Magnuson-Moss Warranty Act. All other warranties, whether expressed or implied, including without limitation any warranty of merchantability or fitness for purpose are expressly disclaimed.

LIMITATIONS

- This product requires skilled application.
- Surface air and substrate temperature must be 40°F or higher during application and for 24 hours thereafter.
- CHIFFON is not compatible with solvent based coatings and cleaners.
- Wear face and eye protection during application.
- Use in a well ventilated area.
- Not recommended for walls where high commercial traffic and surface abrasion is expected.

The logo for PermaTone features the word "Perma" in a bold, blue, sans-serif font. The word "Tone" is written in a vibrant, multi-colored gradient (red, orange, yellow, green, blue) and is slightly larger and more stylized than "Perma".

PermaTone, Inc.

11620 Brittmoore Park Drive

Houston, Texas 77041

832/243-0787 TEL

713/937-9765 FAX

www.permatone.com

PermaTone and the PermaTone logo are registered trademarks of PermaTone, Inc.