

PermaTone QuartzMural™

QuartzMural

An elegant acrylic texture coating. It is durable, permeable, mildew resistant and easy to maintain.

RECOMMENDED USE

QUARTZMURAL is used as an alternative to traditional wall covering like vinyl, wallpaper, paint or textured drywall compound. It is ideal for use in high traffic areas and areas where mildew is present.

QUARTZMURAL can be applied over properly prepared drywall, CMU block, plaster or concrete.

COVERAGE

Each 5 gal. pail provides approximately 130-150 ft² of coverage. However, variances in substrate and application technique will affect coverage.

PACKAGING

5 gal. pail: 66 lbs. net, 68.8 lbs. gross

COLORS

QUARTZMURAL can be matched to almost any custom color.

PROPERTIES

Drying Time

Initial Set: 4 hrs. @ 70°F, 50% RH

Cure: 24 hrs. @ 70°F, 50% RH

APPLICATION

Surface Preparation

Surface must be paint ready, clean and dry; free of dust, grease or other materials that may affect bonding. Previously painted surfaces must be scraped to remove all loose paint. Vinyl wall coverings and wallpaper must be removed along with any excess adhesive. Use COREVMIX surface leveler to repair surface imperfections and skim over adhesive residue. Prime with PINTUFONDO in the desired base color. Allow PINTUFONDO to dry for at least 12 hours before beginning QUARTZMURAL application.

VOC Compliance

QUARTZMURAL complies with all known regulations limiting the Volatile Organic Compound (VOC) content of architectural coatings and sealers. ASTMD 3960 19g/L or .16 lb/gal

Application Procedures

Using a stainless steel trowel, extend QUARTZMURAL onto the previously primed substrate.

Excess material should immediately be removed from the substrate with a stainless steel trowel. This procedure requires the applicator to move the trowel evenly over the surface while holding the trowel at an angle of approximately 10°-15° with the surface. The larger aggregate in the material serves as a built in gauge for controlling the material thickness.

Once the material has been evenly applied and troweled down to the proper thickness, it is ready for texturing. The texture is produced by floating the surface with an acrylic trowel. The trowel will cause the larger aggregate to roll through the finish creating the texture. The arm and hand movement of the applicator determines the final texture. Vertical motion results in a wood grain texture, a circular motion will result in a swirl texture. Constantly clean the acrylic trowel with a moist sponge to avoid material build-up.

CLEAN-UP

Tools should be cleaned with water while QUARTZMURAL is still wet.

STORAGE

Store QUARTZMURAL in its original container at temperatures not less than 40°F (4°C) or greater than 110°F (43°C). Store out of direct sunlight. Do not stack pails more than three high.

MAINTENANCE

QUARTZMURAL may be cleaned of minor deposits with a medium bristle brush and a mild soap and water solution. Major soiled surfaces may be re-coated with PINTUFONDO.

SHELF LIFE

Approximately one year if stored properly.

WARRANTY

QUARTZMURAL is conditionally warranted for 10 years against delamination, color fading, and mildew growth. FOR COMPLETE INFORMATION, CONSULT PERMATONE'S LONG FORM SPECIFICATIONS AND PRODUCT WARRANTIES. This warranty does not apply to any party constituting a "consumer" for purposes of the Magnuson-Moss Warranty Act. All other warranties, whether expressed or implied, including without limitation any warranty of merchantability or fitness for purpose are expressly disclaimed.

LIMITATIONS

- Surface air and substrate temperatures must be 40°F or higher during application and for a period of 24 hrs. thereafter.
- QUARTZMURAL is not compatible with solvent base products or cleaners.
- Use in well ventilated areas. Protect all adjacent surfaces (door frames, windows, etc.) adequately. Do not water down material. Do not apply over quickset joint compound. Prepare metal surfaces such as corner bead with rust inhibitors prior to QUARTZMURAL application.
- This product requires skilled application.
- Use eye and face protection.
- Avoid constant moisture in the wall cavity behind the coating.



PermaTone, Inc.

11620 Brittmoore Park Drive

Houston, Texas 77041

713/937-3437 TEL

713/937-9765 FAX

800/944-4911 TOLL FREE

www.permatone.com