

# PermaTone® Sabbia

## Sabbia

A Venetian plaster available in a variety of textures that all produce tonal contrasts and visual depth reminiscent of natural limestone. Sabbia is water-based, environmentally safe, mildew resistant, and highly scratch and abrasion resistant, durable, cleanable and easy to maintain.

### RECOMMENDED USE

Interior commercial, hospitality, military, educational and residential wall applications. Sabbia may be applied over properly prepared drywall, CMU block, masonry, plaster or concrete.

### COVERAGE

150-250 ft<sup>2</sup> per 5 gallon pail. Variations in substrate conditions and applicator technique and skill will affect coverage.

### PROPERTIES

#### Drying Time

**Initial Set:** 6 hrs. @ 70°F, 50% RH

**Cure:** 36 hrs. @ 70°F, 50% RH

### VOC Compliance

Sabbia complies with all known regulations limiting the Volatile Organic Compound (VOC) content of architectural coatings and sealers.

### PACKAGING

1 gallon pail: 11 lbs. net, 11.7 lbs. gross

5 gallon pail: 60 lbs. net, 62.8 lbs. gross

### REDUCTION

Use potable water. Material may be diluted with up to 8 oz. of water per 5 gallon pail in order to achieve desired consistency.

### EQUIPMENT

Stainless steel trowel; hawk; acrylic float; paint roller; cotton towel; urethane float; air compressor; hopper. See the PermaTone Application Guide for information on equipment for specific textures.

### APPLICATION

#### Surface Preparation

Surfaces must be smooth, clean, dry, paint ready, and free of dust, grease or other materials that may affect bonding.

Previously painted surfaces must be scraped to remove all loose paint. Vinyl wall coverings and wallpaper must be removed along with any excess adhesive. Use CorevMix surface leveler to repair surface imperfections and to skim over adhesive residue.

Prime with PintuFondo tinted to the desired base color. See surface preparation instructions specific to each texture and related

support products in the PermaTone Application Guide.

### Material Preparation

Mix Sabbia to a homogeneous consistency with a mud mixer at low speed.

### Application Procedures

#### CLASSIC

*Surface imperfections may show through the final finish.* Remove all dust with a moist cloth. Using a brush, roll or spray equipment, prime over the surface with PINTUFONDO. Using a stainless steel trowel, apply the first layer of Sabbia. Avoid ANY material buildup. Each coat thickness should not exceed 20-25 mils (the thickness of the largest aggregate). Allow the first coat to dry 8 to 12 hours before applying a second coat in the same manner as the first. Allow the Sabbia to set up for approximately 30-40 minutes before beginning to texture. To achieve the CLASSIC, smooth and mottled appearance, use a acrylic float and repeatedly float the surface pressing down and sliding the trowels edge over the surface holding a 5° to 10° angle with the surface until it becomes smooth.

The final appearance depends on the experience of the individual applicator.

### OTHER APPLICATION

Sabbia may be applied with a wide variety of tools and techniques to produce a wide variety of textures. Consult the PermaTone Application Guide for instructions on the most popular textures.

### STORAGE

Store Sabbia in its original containers at temperatures not less than 40°F (4°C) or greater than 110°F (43°C). Store out of direct sunlight. Do not stack pails more than three high.

### SHELF LIFE

Approximately one year if stored properly.

### MAINTENANCE

Surface may be cleaned of minor stains with a medium bristle brush or a damp cotton cloth and a mild soap and water solution.

### WARRANTY

Sabbia is conditionally warranted for 10 years against delamination and color fading. FOR COMPLETE INFORMATION, CONSULT PERMATONE'S LONG FORM SPECIFICATIONS AND PRODUCT WARRANTIES.

This warranty does not apply to any party constituting a "consumer" for purposes of the Magnuson-Moss Warranty Act. All other warranties, whether expressed or implied, including without limitation any warranty of merchantability or fitness for purpose, are expressly disclaimed.

### LIMITATIONS

- For use on interior wall and ceiling surfaces only.
- Patching limitations standard to applied coatings.
- This product requires skilled application.
- Surface air and substrate temperatures shall be 60°F to 85°F during application and for a period of 24 hours thereafter.
- Sabbia is not compatible with solvent base products or cleaners.
- Use in well ventilated areas.
- Protect all adjacent surfaces (door frames, windows, etc.) adequately.
- Do not apply over quickset joint compound.
- Prepare metal surfaces such as corner bead with rust inhibitors prior to application of Sabbia.
- Always wear appropriate eye and skin protection when using this product.
- Avoid constant moisture in the wall cavity behind the coating.
- Harmful if swallowed.

Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document. PermaTone assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project.



PermaTone, Inc.

11620 Brittmoore Park

Drive Houston, Texas

77041

832/243-0787 TEL

713/849-9114 FAX

FREE [www.permatone.com](http://www.permatone.com)

Made in the U.S.

03.19

