



## Texture Information Sheet

Product | Sabbia

### Description

A decorative acrylic Venetian plaster with a subtle knockdown appearance.

### Recommended Use

Interior commercial, hospitality and residential applications requiring a knockdown Venetian appearance.

### Colors

All custom; no limitations.

### Packaging

1 gallon pail: 11 lbs. net, 11.7 lbs. gross; 5 gallon pail: 60 lbs. net, 62.8 lbs. gross.

### Approximate Coverage

150-250 ft<sup>2</sup> per 5 gallon bucket.

### Equipment

Stainless steel trowel with rounded corners and beveled edges; air compressor; hopper; knockdown blade; acrylic float.

### Surface Preparation

Surfaces must be smooth, clean, dry and paint ready. Prime surfaces with Pintufondo in the desired base color. See instructions for application of Pintufondo.

### Application Instructions

Using the specified trowel, apply the first layer of Sabbia using short strokes and irregular patterns. The largest aggregate in the coating will determine the thickness of each coat. Avoid any material buildup. Allow to dry 8-12 hours. Apply a second coat to approximately 70-80% of the surface, using the air compressor and hopper with a 1/4" tip and pressure of 25-30 psi. Immediately use the blade to lightly knock down the material, and allow to dry approximately 20-25 minutes before texturing. Float in random directions with an acrylic float held at an approximate 5-10° angle to the surface, until the desired texture is achieved. Material may be diluted with up to 8 ozs. of potable water only per five gallon bucket.

### Properties

Initial set in 6 hours, cure in 36 hours in ideal application conditions of 70°F and 50% RH.

### Benefits

Water based; integral color; environmentally safe; vapor permeable; highly mildew resistant; highly scratch and abrasion resistant.

### Limitations

Patching limitations standard to applied coatings; skilled application required; not compatible with solvents; apply in temperatures between 60°F and 85°F; protect face and eyes; use in well ventilated areas; for use on interior wall and ceiling surfaces only.

### Maintenance

To clean, use a medium bristle brush or damp cloth and a mild soap and water solution.

### Warranty

10 years material warranty against delamination and color fading.

- Always prepare a mock-up of minimum 4' x 4' for approval prior to application to subject wall areas. The mock-up serves two purposes, to establish coverage and material requirements and to establish owner's expectations as to the appearance of the texture. Coverage varies according to substrate conditions and applicator technique and skill level.
- The application instructions described herein represent the most typical methods currently used, but are in no way intended to restrict the designer, contractor or faux finisher in terms of creating new patterns, effects or textures using PermaTone products. Instructions as to surface preparation and reduction should be followed precisely, however, in order not to void the warranty.
- PermaTone products should never be mixed with other materials, with the exception of clean, potable water, and then only where indicated as acceptable in this or other PermaTone product information documents.
- Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document. PermaTone assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project.
- Most equipment described in this document may be purchased from PermaTone or its distributors.

Antique Dragged