



Texture Information Sheet

Product | **Tevere**

Description

An acrylic Venetian plaster; matte, rustic appearance with voids showing contrasting color undercoat.

Recommended Use

Interior commercial, hospitality and residential applications requiring dramatic matte accents.

Colors

All custom; no limitations.

Packaging

1 gallon pail: 11 lbs. net, 11.7 lbs. gross; 5 gallon pail: 56 lbs. net, 58.8 lbs. gross.

Approximate Coverage

300-450 ft² per 5 gallon bucket.

Equipment

Roller; hawk; stainless steel trowel with rounded corners and beveled edges; sponge; knockdown blade.

Surface Preparation

Surfaces must be smooth, clean, dry and paint ready. Prime surfaces with Pintufondo in the desired base color. See instructions for application of Pintufondo.

Application Instructions

Trowel apply a thin, tight coat of QuartzSilco over the entire surface. Allow to dry approximately 4 to 6 hours, depending on room temperature and humidity. Dab on Tevere using any one of a variety of tools, the most common of which are the sponge and the stainless steel trowel with beveled edges. Do not fully cover the surface with Tevere; leave voids so that the color of the QuartzSilco remains visible and that the surface of the Tevere will not be uniformly smooth. Use the knockdown blade in random directions to flatten the surface. Wait approximately 15 to 20 minutes, depending on room temperature and humidity. Repeatedly press down and slide the trowel edge in random directions over the surface, holding a 5-10° angle to the surface. Apply a second coat of Tevere in the same manner as the first, following instructions above for leaving voids, knocking down, and burnishing.

Properties

Initial set in 30 minutes, cure in 72 hours, at 70°F and 50% RH.

Benefits

Water based; integral color; environmentally safe; vapor permeable; highly mildew resistant.

Limitations

Patching limitations standard to applied coatings; skilled application required; not compatible with solvents; apply in temperatures between 60°F and 85°F; protect face and eyes; use in well ventilated areas; for use on interior wall and ceiling surfaces only.

Maintenance

Surface may be cleaned of minor stains with a damp cotton cloth.

Warranty

10 years material warranty against delamination, color fading and mildew growth.

- Always prepare a mock-up of minimum 4' x 4' for approval prior to application to subject wall areas. The mock-up serves two purposes, to establish coverage and material requirements and to establish owner's expectations as to the appearance of the texture. Coverage varies according to substrate conditions and applicator technique and skill level.
- The application instructions described herein represent the most typical methods currently used, but are in no way intended to restrict the designer, contractor or faux finisher in terms of creating new patterns, effects or textures using PermaTone products. Instructions as to surface preparation and reduction should be followed precisely, however, in order not to void the warranty.
- PermaTone products should never be mixed with other materials, with the exception of clean, potable water, and then only where indicated as acceptable in this or other PermaTone product information documents.
- Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document. PermaTone assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project.
- Most equipment described in this document may be purchased from PermaTone or its distributors.

Galapagos