



Permatone, Inc
11620 Brittmoore Park Drive
Houston, TX 77041

RE: QuartzSilco Interior textured finishes VOC Statement

QuartzSilco is an Acrylic polymer based interior textured coating which can be applied to create a variety of Textured looks.

QuartzSilco is formulated to be an environmentally friendly, low VOC product and application. The following Table summarizes the VOC Data for the two component products of the QuartzSilco System:

KTA-1: Pintufondo – 100 Primer; Batch# 4733; PermaTone Inc. Tuesday, July 5, 2011		
Determination	Method	Results
Density	ASTM D 1475	15.82 lbs/gal
Weight Solids	ASTM D 2369	83.04%
Water Content	ASTM D 4017	15.73%
VOC Content Calculation	ASTM D 3960	33 g/L or 0.28 lb/gal
KTA-2: Quartzsilco – 100 Texture; Batch# 4700; PermaTone Inc. Tuesday, July 5, 2011		
Determination	Method	Results
Density	ASTM D 1475	15.87 lbs/gal
Weight Solids	ASTM D 2369	83.23%
Water Content	ASTM D 4017	16.09%
VOC Content Calculation	ASTM D 3960	19 g/L or 0.16 lb/gal

PINTUPRIME _ Is a high solids , high permeability undercoat for the QuartzSilco Textured finish

PERMANTONE, INC