

# PermaTone™ CorevBase™

## CorevBase

A flexible acrylic basecoat used primarily as a floating compound to level surfaces or fill gaps prior to application of PermaTone Walltexture Designs.

### RECOMMENDED USE

Interior commercial, hospitality, military, educational and residential wall applications. CorevBase provides hardness, low absorption, and adhesion to diverse surfaces such as CMU block, brick, tile, textured walls, and glazed brick.

### COVERAGE

120-160 ft<sup>2</sup> per 5 gallon pail. Variations in substrate conditions and applicator techniques will affect coverage.

### PROPERTIES

#### Drying Time

**Initial Set:** 4 hrs. @ 70°F, 50% RH

**Cure:** 24 hrs. @ 70°F, 50% RH

#### VOC Compliance

CorevBase complies with all known regulations limiting the Volatile Organic Compound (VOC) content of architectural coatings and sealers.

#### PACKAGING

5 gallon pail: 66 lbs. net, 68.8 lbs. gross

#### REDUCTION

Use potable water. Material may be diluted with up to 8 oz. of water per 5 gallon pail in order to achieve desired consistency.

#### EQUIPMENT

Stainless steel trowel; hawk

### APPLICATION

#### Surface Preparation

Surface must be clean, dry, and free of dust, grease, or other materials that may affect bonding. Previously painted surfaces must be scraped to remove all loose paint.

#### Material Preparation

Mix CorevBase to a homogeneous consistency with a mud mixer at low speed.

#### Application Procedures

Apply the first coat with a stainless steel trowel. Allow the product to dry 12 to 18 hours and apply the second coat as required to level the surface. The first coat will tend to crack when filling deep voids. Fill such cracks with subsequent coats. When product is dry, sand the surface with #80 or #100 sandpaper if it is necessary. Remove any residual dust before applying other materials.

#### STORAGE

Store CorevBase in its original container at temperatures not less than 40°F (4°C) or greater than 110°F (43°C). Store out of direct sunlight. Do not stack pails more than three high.

#### SHELF LIFE

Approximately one year if stored properly.

#### WARRANTY

CorevBase is conditionally warranted for 10 years against delamination and mildew growth. FOR COMPLETE INFORMATION, CONSULT PERMATONE'S LONG FORM SPECIFICATIONS AND PRODUCT WARRANTIES. This warranty does not apply to any party constituting a "consumer" for purposes of the Magnuson-Moss Warranty Act. All other warranties, whether expressed or implied, including without limitation any warranty of merchantability or fitness for purpose are expressly disclaimed.

### LIMITATIONS

- For use on interior walls and ceiling surfaces only.
- This product requires skilled application.
- Surface air and substrate temperatures shall be 60°F to 85°F during application and for a period of 24 hours thereafter.
- CorevBase is not compatible with solvent base products or cleaners.
- Use in well ventilated areas.
- Protect all adjacent surfaces (door frames, windows, etc.) adequately.
- Do not apply over quickset joint compound.
- Prepare metal surfaces such as corner bead with rust inhibitors prior to application of CorevBase.
- Always wear appropriate eye and skin protection when using this product.
- Avoid constant moisture in the wall cavity behind the coating.
- Harmful if swallowed.

Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document. PermaTone assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project.

The logo for PermaTone, featuring the word "Perma" in a bold, blue, sans-serif font and "Tone" in a red, cursive script font.

**PermaTone, Inc.**

11620 Brittmoore Park Drive

Houston, Texas 77041

832/243-0787 TEL

713/849-9114 FAX

[www.permatone.com](http://www.permatone.com)

Made in the U.S.

