

PermaTone CorevMix™

CorevMix

A permeable, finely ground, acrylic base material for use under PermaTone products such as Palladio, Tevere and Marmolino.

RECOMMENDED USE

Provides hardness and adhesion to diverse surfaces, with high stability and coverage. It's a smooth, breathable and flexible base

COVERAGE

Each 5-gallon bucket provides 200-250 square feet of coverage. Maximum thickness wet: 30 mils. Variations in substrate conditions and applicator technique and skill level will affect coverage.

PACKAGING

1 gal. Pail 11.5 lbs. net, 11.9 lbs gross
5 gal. Pail 60 lbs. net, 62.8 lbs gross

PROPERTIES

Drying Time:

Initial Set: 1-2 hrs. @ 70°F, 50% RH

Cure: 72 hrs. @ 70°F, 50% RH

VOC Compliance:

CorevMix complies with all known regulations limiting the Volatile Organic Compound (VOC) content of architectural coatings and sealers.

EQUIPMENT

Hawk; stainless steel trowel (alternately, taping tools); Stainless steel trowels or spatulas spatula, sandpaper # 250 or/and # 320

APPLICATION

Surface Preparation

Surface must be clean, dry and free of dust, grease or other irregular materials. Previously painted surfaces shall be scraped to remove all loose paint. Avoid damage to the substrate during paint removal. Vinyl wall coatings and wallpaper must be removed along with any excess paste

Material Preparation

Mix CorevMix with a drill with low rpm

Application Procedure

Apply CorevMix with trowel or spatula spreading the material. Do not try to smooth the product in the application in one layer, this can only make cracks in product. Let dry 4 to 6 hours and apply as many layers as needed. When product is dry, sand the area. Eliminate dust before applying any other material.

CLEAN-UP

Tools and should be cleaned with water while CorevMix is still wet.

STORAGE

Store Castello in its original container at temperatures not less than 40°F (4°C) or greater than 90°F (32°C). Store out of direct sunlight. Do not stack pails more than three high.

SHELF LIFE

Approximately one year if stored properly.

MAINTENANCE

Surface may be cleaned of minor stains with a damp cotton cloth.

WARRANTY

CorevMix is conditionally warranted for 5 years against delamination and color fading. This warranty does not apply to any party constituting a "consumer" for purposes of the Magnuson-Moss Warranty Act. All other warranties, whether expressed or implied, including without limitation any warranty of merchantability or fitness for purpose, are expressly disclaimed.

LIMITATIONS

- For use on interior and exterior wall surfaces only.
- Patching limitations standard to applied coatings.
- This product requires skilled application.
- Surface air and substrate temperatures shall be 60°F to 85°F during application and for a period of 24 hours thereafter.
- CorevMix is not compatible with solvent base products or cleaners.
- Use in well ventilated areas.
- Protect all adjacent surfaces (door frames, windows, etc.) adequately.
- Do not water down material.
- Do not apply over quickset joint compound.
- Always wear appropriate eye and skin protection when using this product.
- Harmful if swallowed.
- Avoid constant moisture in the wall cavity behind the coating.

Information contained in this bulletin conforms to the standard detail recommendations and specifications for the installation of PermaTone products, is presented in good faith, and is applicable as of the date of this document.

PermaTone assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project.

The logo for PermaTone, featuring the word "Perma" in blue and "Tone" in red, with a stylized red swoosh above the "e" in "Tone".

PermaTone, Inc.

11620 Brittmoore Park
Drive Houston, Texas
77041 713/937-3437 TEL
713/849-9114 FAX

www.permatone.com

Made in the U.S.